

Product range - BLACK PROFIL, s.r.o

Steel open sections

L shape

min. L 20/15 x th.

max. L 180/100 x th.

U shape

min. U 16/25/16 x th.

max. U 120/300/120 x th.

(width 25-300 mm, height 16-120 mm)

C shape

min. C 10/30/30/30/10 x th.

max. C 15/40/280/40/15 x th.

(width 30-280 mm, height 25-120 mm)

Thickness

1,5 - 6 mm

Section length

500 - 14.000 mm

Material

S 235, S 355, DC 01, DX51D+Z275, S 235 pickled,....

BLACK PROFIL, s.r.o.

735 34 Stonava 1064

e-mail: obchod@blackprofil.cz

web: blackprofil.cz

IČ: 278 06 898 DIČ: CZ 278 06 898

Specialized open steel sections

width 50-300 mm

height 15-120 mm

Width of input material

max. 640 mm

L, U, C section thickness

2,5 - 6 mm

Section length

500 - 14.000 mm

Material

S 235, S 355, DC 01, DX51D+Z275, S 235 pickled,....

BLACK PROFIL, s.r.o.
735 34 Stonava 1064

e-mail: obchod@blackprofil.cz
web: blackprofil.cz

IČ: 278 06 898 DIČ: CZ 278 06 898

Closed steel sections

Square

min. □ 15 x 15 x th.

max. □ 200 x 200 x th.

Rectangular

min. □ 25 x 15 x th.

max. □ 300 x 100 x th.

Tubes

min. ○ 17 x th.

max. ○ 273 x th.

Section thickness

1,2 - 8 mm

Section length

500 - 14.000 mm

Material

S 235, S 355, DC 01, DX51D+Z275, ...

Removal of spillage from closed steel sections

We now offer the removal of spillage from closed welded sections. During welding, spillage occurs, which we can remove even after some time has passed since production, thanks to newly developed technology.

Square

min. min. □ 35 x 35 x th.max. □ 80 x 80 x th.

Rectangular

min. min. □ 35 x 35 x th.max. □ 80 x 80 x th.

Section length

500 – 2.900 mm

Material

S 235, S 275, S 355

Section thickness

1,5 - 6 mm